

FEDERATION INTERNATIONALE DE L'AUTOMOBILE

Form of recognition in accordance with
Appendix J to the International Sporting Code.


Manufacturer DAF
Serial N° of chassis .. 5592 ..
engine .. B110 ..
Recognition is valid from .. 14 March 68 List . 1968/4

Cylinder-capacity ... 1108...cm³ .. 67.61..in³

Model 55 ..
Manufacturer DAF ..
Manufacturer

The manufacturing of the model described in this recognition form was started on .. Sept. .. 19 67 and the minimum production of .. 1000 .. identical cars, in accordance with the specifications of this form was reached on 13-12-67. 19 ..

Photograph A , 3/4 view of car from front



The vehicle described in this form has been subject to the following amendments :

Variants

		<u>Normal evolution of the type</u>			
on	19 .. rec.N°.....	List	on	19 .. rec.N°	List
on	19 .. rec.N° ..	List ..	on	19 .. rec.N°	List ..
on	19 .. rec.N°	List ..	on	19 .. rec.N°	List ..
on	19 .. rec.N°	List ..	on	19 .. rec.N°	List ..
on	19 .. rec.N°	List ..	on	19 .. rec.N°	List ..

Stamp and signature of the
National Sporting Authority

Stamp and signature of the F.I.A.

Hubertphor

Page

INTERNATIONAL
FEDERATION
DE L'AUTOMOBILE
F.I.A.

Make ... DAF


Model . 55

... P.T.A. Rec. No.


Photograph B , 3/4 view of
the car from rear.




Photograph D, front axle complete,
without wheels, removed from the car




Photograph F, front brake ,
drum removed.



Photograph C , interior view of
car through driver's door (open or main
door) v. 1970



Photograph E, rear axle complete,
without wheels, removed from the car.



Photograph G, rear brake ,
drum removed.




DAF

Photograph H


gear-box , view from side.

See photograph E


Photograph J



Photograph L




Photograph N




Photograph I




Photograph K



Photograph M




Photograph O





Page 30

Technical Details


PRINTED IN U.S.A.
BY THE GOVERNMENT OF THE
UNITED STATES OF AMERICA
FOR THE NATIONAL BUREAU OF STANDARDS





Indicate scale or dimensions.
Drawing exhaust and inlet
ports of cylinder-head.



Indicate scale or dimensions.
Drawing exhaust manifold
ports, side of cylinderhead.



Indicate scale or dimensions.
Drawing intake manifold ports,
side of cylinderhead.



Photograph 2

Photograph 3

Model 55 DAB DATE

Make DAF

Model 55

F.I.A. Rec. N°

SUSPENSION

70. Front suspension (photogr. D), type Independent, longitudinal torsion bar
 71. Type of spring torsion
 72. Stabiliser (if fitted) yes
 73. N° of shockabsorbers 2 74. Type telescopic double-acting hydraulic
 78. Rear suspension (photogr. E), type Independent swing axles
 79. Type of spring coil
 80. Stabiliser (if fitted) no
 81. N° of shockabsorbers 2 82. Type telescopic double-acting hydraulic

BRAKES (photographs F and G)

		Front	Rear
		mm	in.
94. Number of cylinders per wheel	1		1
95. Bore of wheel cylinder(s)			17,46 mm 0.687 in.
Drum brakes		mm	in.
96. Inside diameter		mm	200 mm 7.87 in.
97. Length of brake linings		mm	196 mm 7.72 in.
98. Width of brake linings		mm	40 mm 1.57 in.
99. N° of shoes per brake			2
100. Total area per brake		mm ²	157 mm ² 24.34 in ²
Disc brakes		mm	in.
101. Outside diameter	248	mm	9.75 in.
102. Length of brake linings	55	mm	2.17 in.
103. Width of brake linings	37	mm	1.46 in.
104. N° of pads per brake	2	mm ²	mm ² in ²
105. Total area per brake	2x2000	6.2	in ²



• Make

DAF

Model 55

T.I.L. Doc.


ENGINE (photographs J and K)

130. Cycle	4	131. No. of cylinders	4
132. Cylinder arrangement	in line		
133. Bore	70 mm 2.756 in.	134. Stroke	72 mm 2.835 in.
135. Capacity per cylinder	277 cm ³	136. Total cylinder-capacity	16.9 cu. in.
137. Material(s) of cylinder-block	cast iron		
138. Material(s) of sleeves (if fitted)	steel		
139. Cylinder-head, material(s)	aluminium		No fitted 1
140. Number of inlet ports	4	141. Number of exhaust ports	4
142. Compression ratio	8,5:1		
143. Volume of one combustion chamber	31,17 cm ³	144. Piston, material(s)	1.963 cu. in.
145. Distance from gudgeon pin centre line to highest point of piston crown	40 mm	146. Type of crankshaft	1.57 inches 4 throw
147. Crankshaft : moulded / stamped		148. Number of crankshaft main bearings	5
149. System of lubrication : anyways / oil in sump		150. Capacity, lubricant	2,5 ltrs 4.40 pints 2.64 quarts UK
151. Oil cooler : xxx / no		152. Method of engine cooling; water	
153. Capacity of cooling system	4,8 ltrs	154. Cooling fan (if fitted), dia.	8.45 pints 5.07 quarts UK
155. Connecting rod big end, type plain	28 cm	156. Number of blades of cooling fan	11.02 inches
			6
Bearings			
157. Crankshaft main, type plain		Dia.	46 mm 1.811 in.
158. Connecting rod big end, type plain		Dia.	43,9 mm 1.731 in.
Weights			
159. Flywheel (clean)	7,83 ^{+0,01} kg	160. Flywheel with clutch (all turning parts)	12,796 kg lbs
161. Crankshaft	8,2 ^{+0,2} kg	162. Connecting rod	0,46 ^{+0,03} kg lbs
163. Piston with rings and pin	0,36 ^{+0,01} kg		

Make DAF model 55

FOUR STROKE UNICYL.

170. N° of camshafts 1 171. Location LH side
172. Type of camshaft drive chain driven engineblock
173. Type of valve operation push-rod



INTAKE (see page 4)*

180. Material(s) of inlet manifold aluminium
181. Diameter of valves 31 mm 1.22 inches
182. Max. valve lift 7,15 mm 0.281 inches 183. N° of valve springs 1
184. Type of spring coil 185. N° of valves per cylinder 1
186. Tappet clearance for checking timing (cold) 0,15 mm .0059 inches
187. Valves open at (with tolerance for tappet clearance indicated))
188. Valves close at (with tolerance for tappet clearance indicated))
189. Degrees of crankshaft rotation from zero to - } see diagram
maximum valve lift 3/4 maximum valve lift }
190. Air filter, type dry

EXHAUST (see page 4)

195. Material(s) of exhaust manifold cast iron
196. Diameter of valves 26,8 mm 1.06 inches
197. Max. valve lift 7,09 mm 0.280 inches 198. N° of valve springs 1
199. Type of spring coil 200. N° of valves per cylinder 1
201. Tappet clearance for checking timing (cold) 0,20 mm .0079 inches
202. Valves open at (with tolerance for tappet clearance indicated))
203. Valves close at (with tolerance for tappet clearance indicated))
204. Degrees of crankshaft rotation from zero to - } see diagram
maximum valve lift 3/4 maximum valve lift }

CARBURETION (photograph N)

210. N° of carburetors fitted 1 211. Type horizontal
212. Make Solex 213. Model 32 EHSA
214. Flange hole diameter of exit port(s) of carburetor 32 mm 1.26 in.
215. Minimum diameter of air-passage 26 mm 1.02 in.

FUEL INJECTION (if fitted)

220. Make of pump 221. N° of plungers
222. Model or type of pump 223. Total n° of injectors
224. Location of injectors

*) For additional information concerning two-stroke engines and supercharged engines see page 13.

ENGINE ACCESSORIES

230. Fuel pump : mechanical ~~and/or electric~~ 231. H.P. fitted 1
232. Type of ignition system coil 233. No. of distributors 1
234. N° of ignition coils 1 235. N° of spark plugs per cylinder 1
236. Generator, number fitted 1 237. Method of drive belt
238. Voltage of generator 12 volts 239. Battery, number 1
240. Location under bonnet
241. Voltage of battery 12 volts

ENGINE AND CAR PERFORMANCE (as declared by manufacturer in catalogue)

250. Max. engine output 45 (type of horsepower: DIN) at 5000 rpm.
251. Maximum rpm 5500 output at that figure
252. Maximum torque 8,0 mkg at 2800 rpm
253. Maximum speed of the car 136 km/hour 85 miles/hour

SAFETY & RELIABILITY
AND PERFORMANCE OF
DAF CARS

Optional equipment affecting pricing information

- sump guard
- additional fuel tank 20 L.
- Triplex glass windscreen
- Alternator

© 1994 Daimler-Benz AG
Daimler-Benz AG